

CE 105

Corrosion of metals



Description

- principles of corrosion and corrosion protection on metallic materials
- oxygen corrosion
- electrochemical corrosion (local elements)
- corrosion protection with external voltage and sacrificial anodes

Corrosion damage to metallic components causes considerable economic and technical damages. The issue of corrosion and corrosion protection therefore plays an important role in technical training.

The CE 105 allows a variety of factors that influence corrosion processes to be investigated in parallel. Eight glass vessels are available to do this. They allow different materials to be compared under different conditions. The required electrolyte solution is added to the vessels. Up to six specimens can be attached to the cover of each vessel and these are immersed in the solution.

It is possible to connect specimens to an electrical conductor to investigate local elements and the principle of sacrificial anodes. An adjustable power pack allows an external voltage to be connected. This counters the current flow between precious and base metals in local elements. As result the corrosion rate of the more base metal is reduced.


A diaphragm pump conveys ambient air into the electrolyte solution as required. Flow control valves can be used to individually adjust the gas flow rate for each vessel. It is also possible to feed other gases provided by the laboratory into the electrolyte solution. A pH meter is included to allow the influence of the electrolyte solution on corrosion processes to be investigated and compared.

Learning objectives/experiments


- corrosion behaviour of different metallic materials (rust / passivation)
- formation of local elements
- influence of pH value of the electrolyte solution
- influence of salt concentration in the electrolyte solution
- oxygen corrosion
- corrosion protection
 - ▶ external voltage
 - ▶ sacrificial anodes
 - ▶ protective layers

CE 105


Corrosion of metals



1 electrical connecting sockets, 2 electrolyte vessel with specimens and specimen holders (clamps), 3 electrolyte vessel with specimen holders (hooks), 4 flow control valves, 5 gas supply, 6 power pack, 7 diaphragm pump switch, 8 air / external gas supply reversing valve



Experimental result: a steel specimen (2) and a copper specimen (3) were electrically connected (4) and supplied with an external voltage. A steel specimen (1) with no electrical connection was used as a reference.



Two corrosion types: a surface corrosion, b pitting

Specification

- [1] investigation of corrosion and corrosion protection measures
- [2] 8 electrolyte vessels with covers and 6 specimen holders each
- [3] adjustable power pack for application of external voltage
- [4] air supply via diaphragm pump
- [5] reversing valve for air or external gas supply
- [6] adjustment of gas flow rate for each vessel using flow control valves
- [7] recording of pH value of electrolyte solutions using manual unit
- [8] pressure range for external gas supply: 0,2...1,0bar

Technical data

Electrolyte vessels

- capacity: 1000mL
- material: glass

Power pack

- voltage: 0...30VDC
- current: 0...5A

Diaphragm pump: approx. 260L/h

pH meter

- measuring range: 0...14pH
- resolution: 0,01pH

Specimens

- 6x stainless steel, steel, copper, brass, aluminium
- 3x glass
- dimensions: 100x15x1 mm

230V, 50Hz, 1 phase

230V, 60Hz, 1 phase; 120V, 60Hz, 1 phase

UL/CSA optional

LxWxH: 1280x460x630mm (experimental unit)

Weight: approx. 55kg

LxWxH: 730x480x240mm (storage system)

Weight: approx. 15kg

Scope of delivery

- 1 experimental unit
- 1 pH meter
- 1 set of specimens
- 1 set of laboratory cables
- 1 coupling to connect an external gas supply
- 1 storage system
- 1 set of instructional material

CE 105

Corrosion of metals

Optional accessories

020.30009 WP 300.09 Laboratory trolley