

CE 320

Stirring



The illustration shows a similar unit.

Learning objectives/experiments

- flow fields of various stirrer types
- power demand, mixing time, mix quality dependent on
 - ▶ stirrer type
 - ▶ speed
 - ▶ materials used (density, viscosity)
 - ▶ insertion of flow impeders
- observation of the suspension state of suspended solids when using different stirrers and at different speeds
- observation of the droplet size of emulsions when using different stirrers and at different speeds

Description

- visualisation of flow fields when using various stirrer types
- high-performance stirring machine with speed control
- determination of mixing time of solutions
- mixing of emulsions and suspensions
- power demand during stirring

During stirring, the continuous phase is liquid. With CE 320, the production of solutions (solid dissolved in liquid), emulsions (mixture of immiscible liquids) and suspensions (insoluble solid in liquid) can be investigated.

Mixing takes place in a tank which is resistant to chemicals and heat-resistant. With the high-performance stirring machine even high-viscosity mixtures can be produced. The speed is adjustable. The torque is indicated on the unit's digital display. This enables the power demand to be determined.


Nine different, easily interchangeable stirrers are provided. With plastic balls which are dispersed in the fluid it is possible to observe the characteristic flow fields of the different stirrer types.

Flow impeders can be inserted in the tank to investigate their influence on the mixing process. To determine the mixing time and mix quality of solutions, a conductivity meter is available. The device can also be used to measure temperatures.


A removable coiled tube serves as a heat transfer medium. It can be used for heating or cooling with water from the laboratory supply. A valve with precise adjustment is used to adjust the flow rate. This enables the influence of temperature changes on the mixing process to be investigated, e.g. due to fluid viscosity depending on temperature.

CE 320


Stirring



1 outlet valve, 2 flow impeder, 3 coiled tube, 4 coiled tube valve, 5 stirring machine with speed and torque indicator, 6 turbine stirrer and threaded shaft for stirring heads, 7 stirring elements (8 in total), 8 switch box



Stirring elements: 1,3,8 propeller stirrers, 2,5,6 blade stirrers, 4,7 propeller stirrers, angled



Flow fields in the stirred tank with axial-conveying stirrer (A) and radial-conveying stirrer (B)

Specification

- [1] investigation of mixing processes during stirring
- [2] transparent stirred tank with 4 removable flow impeders
- [3] speed-controlled stirring machine with digital torque indicator
- [4] 9 interchangeable stirrers: axial-, radial-, tangential-conveying
- [5] removable coiled tube for cooling or heating with external water supply
- [6] portable device for measuring conductivity and temperature

Technical data

Stirred tank

- capacity: approx. 15L
- material: DURAN glass and PVDF (base)

Stirring machine

- speed: 50...2000min⁻¹
- max. power output on shaft: 100W

Stirrer elements

- 5 propeller stirrers
 - ▶ 2x 3 blades, Ø=70mm / 100mm
 - ▶ 1x 4 blades, Ø=70mm
 - ▶ 2x 2 blades (angled), Ø=70mm / 100mm
- 3 blade stirrers
 - ▶ 2x Ø=70mm with 3 / 6 holes
 - ▶ 1x Ø=100mm with 10 holes
- 1 turbine stirrer with shaft: Ø=50mm

Coiled tube

- diameter: approx. 140mm
- material: stainless steel

Measuring ranges

- conductivity: 0...200mS/cm
- temperature: 0...85°C
- speed: 50...2000min⁻¹

230V, 50Hz, 1 phase
 230V, 60Hz, 1 phase
 120V, 60Hz, 1 phase
 UL/CSA optional
 LxWxH: 850x600x1950mm
 Weight: approx. 83kg

Required for operation

water connection, drain

Scope of delivery

- 1 experimental unit
- 9 different stirring elements
- 1 set of accessories
- 1 conductivity meter
- 1 packing unit of plastic balls
- 1 set of instructional material