

HL 350

Oil burner demonstrator



Learning objectives/experiments

- layout and operating behaviour of an oil burner
- operation of a heating boiler with an oil burner
- effect of burner setting on combustion and on the flame
- temperature measurements in different areas of the combustion chamber
- oil pressure measurements on the burner with observation of the effects of changes on the flame
- investigation of the effect of oil pre-heating on combustion and particularly the flame
- calculation of the heating capacity of a heating boiler
- function of a plate heat exchanger
- temperature curves in a plate heat exchanger

Description

- **trainer for oil burner test**
- **can be extended to form a complete heating system**
- **viewing window for observing the flame**

The unit is equipped with an oil burner. The oil pressure at the burner, the combustion chamber temperature, measured with a thermocouple, and the pre-heat temperature of the oil are indicated on an additional digital measuring unit. A small oil tank is fitted on the lower shelf of the frame.

The heating boiler features a viewing window for observing the flame. The heat generated can be dissipated using a plate heat exchanger and additional cooling water connections, enabling the unit to be operated continuously.

The exhaust gas can be studied in detail with the exhaust gas analyser HL 860.

HL 350

Oil burner demonstrator



1 measuring amplifier with digital displays, 2 boiler control unit, 3 heating boiler with viewing window, 4 thermocouple, 5 double-strand oil filter, 6 oil tank, 7 expansion vessel, 8 cold water connection, 9 water meter, 10 plate heat exchanger, 11 thermometer, 12 safety group

Specification

- [1] functional heating boiler with oil burner
- [2] boiler with control unit
- [3] boiler casing equipped with a viewing window made of special glass
- [4] heating and cooling circuit equipped with expansion vessel, pump, boiler safety group, thermometers, water meter, heat exchanger
- [5] transparent oil tank with filling and bleed connections
- [6] dissipation of generated heat via plate heat exchanger and cold water connection

Technical data

Boiler

- nominal rating: 17...21kW
- control unit with temperature limiter

Burner

- nominal power: approx. 18kW

Pump

- power consumption: 60W
- max. flow rate: 60L/min
- max. head: 4m

Plate heat exchanger

- capacity: 3kW
- 10 plates

Boiler safety group in accordance with DIN 4751

- 2,5bar
- 50kW

Oil tank: 15L

Water meter: 2,5m³/h

Measuring ranges

- pressure: 1...25bar (oil admission pressure)
- temperature:
 - ▶ 1x 0...1200°C
 - ▶ 1x -50...400°C
 - ▶ 1x 0...120°C
 - ▶ 3x 0...80°C

230V, 50Hz, 1 phase

230V, 60Hz, 1 phase

120V, 60Hz, 1 phase

LxWxH: 1560x800x2000mm

Weight: approx. 269kg

Required for operation

water connection, drain
ventilation & exhaust gas routing required

Scope of delivery

- 1 trainer
- 1 manual

HL 350

Oil burner demonstrator

Optional accessories

065.86000 HL 860 Exhaust gas analyser