

# HM 170.20

## Aerofoil, spring-mounted



### Description

#### ■ model for examination of self-starting vibration in aerodynamics

The aerofoil is suspended flexibly with eight springs in an external frame to permit torsional and transverse vibration of the aerofoil. The frame is simply attached with screws in the measuring section of the wind tunnel. Attachment points on the frame prevent excessive deflection of the aerofoil during the execution of the experiment. The springs can be attached at various positions on the aerofoil and frame in order to set different torsion rigidity levels.

### Learning objectives/experiments

- examination of fluttering vibrations on aerofoils
- the use of a stroboscope permits the observation of the natural forms of the vibrating aerofoil.

### Specification

- [1] aerofoil for examination of self-starting vibration
- [2] profile: symmetrical

### Technical data

Aerofoil NACA 0015

- LxWxH: 200x100x15mm
- weight: 0,157kg
- mass moment of inertia:  
 $1,07 * 10^4 \text{kgm}^2$

Spring rigidity

- single spring: 27N/m
- total rigidity, transverse: 216N/m
- Torsional rigidity: 0,07...0,28Nm/rad

LxWxH: 300x145x120mm

Weight: approx. 3kg

### Scope of delivery

- 1 aerofoil with suspension and frame
- 1 manual

# HM 170.20

## Aerofoil, spring-mounted

Required accessories

070.17000      HM 170      Open wind tunnel