## Simulator Platform

## Comparison Chart



**Entry-Level Simulator** 

Mid-Range Simulators

High-End Simulators











			See	BERTHAN FERNANDE FRANCISCO STANDARDO	3
	OP4512	OP4610XG	OP5705XG	OP5707XG	OP5033XG
Rack Unit	2U	3U	5U	5U	4U
Compatible Software Platforms	RT-LAB   HYPERSIM	RT-LAB   HYPERSIM	RT-LAB   HYPERSIM	RT-LAB   HYPERSIM	RT-LAB   HYPERSIM
Available Software Toolboxes & Add-ons	ARTEMIS eHSx64/32 ePHASORSIM Orchestra RT-XSG	ARTEMIS eHSx64/32 ePHASORSIM Orchestra RT-XSG	ARTEMIS ePHASORSIM EXata CPS Orchestra RT-XSG	ARTEMIS eHSx128/64 ePHASORSIM EXata CPS Orchestra RT-XSG	ARTEMIS ePHASORSIM EXata CPS Orchestra RT-XSG
CPU Family	Intel® Xeon® E3	AMD Ryzen™ 5	2nd Generation Intel® Xeon® Scalable Processors	2nd Generation Intel® Xeon® Scalable Processors	2nd Generation Intel® Xeon® Scalable Processors
CPU Specifications	Available with the following configuration:*  Xeon® 4 cores, 3.7 GHz	Available with the following configuration:* Ryzen™ 6 cores, 3.8 GHz	Available with the following configurations:* Xeon® 4 cores, 2.60 GHz Xeon® 4 cores, 3.80 GHz Xeon® 8 cores, 3.80 GHz Xeon® 16 cores, 3.30 GHz	Available with the following configurations:* Xeon® 4 cores, 3.80 GHz Xeon® 8 cores, 3.80 GHz Xeon® 16 cores, 3.30 GHz	Available with the following configurations:*  Xeon® 4 cores, 2.60 GHz Xeon® 4 cores, 3.80 GHz Xeon® 8 cores, 3.80 GHz Xeon® 16 cores, 3.30 GHz Xeon® 44 cores, 2.10 GHz
XILINX® FPGA	Kintex®-7 410T	Kintex®-7 410T	Artix®-7	Virtex®-7 485T	Artix®-7 (optional)
SFP optical interface (GTX 5 Gbits/s)	4	4	4	16	4 (optional)
I/O modules with 16 analog or 32 digital signals	4	4	8	8	n/a
Available PCI Express Slots for communication cards	1	2	4 or 5**	4 or 5**	5 or 6**
Maximum number of I/O channels	140	140	256	256	n/a

<sup>\*</sup> or equivalent



<sup>\*\*</sup> depending on CPU configuration