

WL 202

Fundamentals of temperature measurement



Description

- **experimental introduction to temperature measurement: methods, areas of application, characteristics**
- **clearly laid out unit primarily for laboratory experiments, also suitable for demonstration purposes**

Recording temperature is one of the basic tasks in metrology. Electric temperature sensors are the most widely used in automation applications but conventional thermometer types are still widely applied in many areas. The WL 202 experimental setup covers the full range of temperature measurement methods. As well as non-electrical measuring methods, such as gas- and liquid-filled thermometers and bimetallic thermometers, all typical electric measuring methods are covered in the experiments. The electrically measured temperatures are displayed directly on programmable digital displays. A temperature-proportionate output voltage signal (0...10V) is accessible from lab jacks, enabling temperature characteristics to be recorded with, for example, a plotter.

For measuring the relative air humidity a psychrometer with two thermometers is available, one of the thermometers measures the dry bulb. The wet bulb thermometer is covered in a wet cotton cloth and measures the evaporative cooling. The temperature difference allows the relative air humidity to be determined.


A digital multimeter with precision resistors is used to calibrate the electrical measuring devices. Various heat sources or storage units (immersion heater, vacuum flask and laboratory heater) permit relevant temperature ranges to be achieved for the sensors being tested. A tool box houses the sensors, cables, temperature measuring strips and immersion heater.

Learning objectives/experiments


- learning the fundamentals of temperature measurement by experimentation
- familiarisation with the various methods, their areas of application and special features
 - ▶ non-electrical methods: gas- and liquid-filled thermometers, bimetallic thermometers and temperature measuring strips
 - ▶ electric methods: thermocouple, resistance temperature detector Pt100, thermistor (NTC)
- determining air humidity with a psychrometer
- calibrating electric temperature sensors

WL 202


Fundamentals of temperature measurement



1 power-regulated socket, 2 laboratory heater for water and sand, 3 psychrometer to determine air humidity, 4 gas pressure thermometer, 5 bimetal thermometer, 6 vacuum flask, 7 mercury thermometer, 8 digital display, thermocouple type K, 9 digital display, thermistor (NTC), 10 digital display, Pt100, 11 multimeter



Temperature measurement with a thermocouple type K: A) nickel chrome, B) nickel; 1 measuring point, 2 tank at constant temperature, 3 reference point, 4 voltmeter



Psychrometer: 1 water tank, 2 wet cotton cloth for covering the wet bulb thermometer, 3 dry bulb thermometer, 4 wet bulb thermometer; dT temperature difference

Specification

- [1] experiments in the fundamentals of temperature measurement with 7 typical measuring devices
- [2] various heat sources or storage units: laboratory heater, immersion heater, vacuum flask
- [3] calibration units: precision resistors and digital multimeter
- [4] liquid, bimetallic and gas pressure thermometers
- [5] temperature sensors: Pt100, thermocouple type K, thermistor (NTC)
- [6] various temperature measuring strips
- [7] psychrometer for humidity measurement
- [8] tool box for sensors, cables, measuring strips and immersion heater

Technical data

Immersion heater

- power output: 300W
- adjustment of power feed via power-regulated socket

Laboratory heater with thermostat

- power output: 450W
- max. temperature: 425°C

Vacuum flask: 1L

Measuring ranges

- resistance temperature detector Pt100: 0...100°C
- thermocouple type K: 0...1000°C
- thermistor (NTC): 20...55°C
- liquid thermometer: -10...250°C
- bimetallic, gas pressure thermometer: 0...200°C
- temperature measuring strips: 29...290°C

Precision resistors: 10 Ω, 100 Ω, 1000 Ω

Psychrometer:

- 2x temperature: 0...60°C
- rel. humidity: 3...96%

230V, 50Hz, 1 phase

230V, 60Hz, 1 phase; 120V, 60Hz, 1 phase

UL/CSA optional

LxWxH: 800x450x650mm

Weight: approx. 45kg

Scope of delivery

- 1 experimental unit
- 1 tool box
- 1 set of cables
- 1 laboratory heater
- 1 immersion heater
- 1 vacuum flask
- 1 digital multimeter
- 1 set of instructional material

WL 202

Fundamentals of temperature measurement

Optional accessories

020.30009

WP 300.09

Laboratory trolley